



China Sanew Cable Co., Ltd.


VDE7717 250°C PFA High Temperature Insulated Wire

<p>Product Features: VDE7717 250°C PFA High Temperature Insulated Wire is resistant to acids, alkalis, oils, flame retardant, fire, and low smoke, no halogen. And the conductor is solid or stranded silver-plated copper or tinned copper conductor, 0.05~5.3 mm². The insulation is color-coded PFA which has standard thickness, and is easy stripping and cutting.</p>	<p>The applications: VDE7717 250°C PFA High Temperature Insulated Wire is widely applied in aviation; Metallurgy and petroleum industry as well as applied in other products such as: electronic instrument & device, electrical appliance, leads for transformer & electrical motor.</p>
---	--

Silver-plated copper or

tinned copper

PFA Teflon Insulation



TECHNICAL DATA:

Conductor:	Silver-plated Copper or Tinned copper
Insulation:	PFA
Temperature Rating:	-80°C to +250°C
Operating Voltage:	450/750V
Conductor stranding:	Please see the next page
Color Code	According to clients
Approvals:	According to VDE, UL

Add: 2-1-101, Binhefang, Daxing District, Beijing, China Zip: 102600 Tel: +86 - 10 - 51265801
E-mail: international@sanew-cable.com Fax: +86 - 10 - 51286576 Website:



China Sanew Cable Co., Ltd.

VDE7717 250°C PFA High Temperature Insulated Wire

Size AWG	Conductor		Insulation (mm)		Maximum Resistance at 20°C Ω/km
	Stranding No./mm	Dia. (mm)	Nominal Thick	Nominal Dia.	
30	1/0.25	0.25	0.20	0.65±0.08	408
	7/0.10	0.30		0.70±0.08	
28	1/0.32	0.32	0.25	0.82±0.08	213
	7/0.12	0.35		0.85±0.08	
26	1/0.40	0.40	0.35	1.10±0.08	138
	7/0.15	0.45			
24	1/0.50	0.50	0.35	1.20±0.08	90.4
	7/0.20	0.60		1.30±0.08	
22	7/0.254	0.76	0.35	1.45±0.11	50.8
	19/0.15	0.80			
20	19/0.19	0.95	0.35	1.65±0.11	33.6
18	19/0.24	1.20	0.35	1.85±0.11	24.6
17	19/0.265	1.40	0.35	2.10±0.11	22.8
16	19/0.30	1.50	0.40	2.30±0.16	16.6
14	19/0.37	1.85	0.40	2.65±0.16	9.5
12	19/0.49	2.40	0.45	3.30±0.20	5.7
11	37/0.38	2.60	0.45	3.50±0.20	4.88
10	37/0.45	3.15	0.50	4.15±0.20	3.64

Add: 2-1-101, Binhefang, Daxing District, Beijing, China Zip: 102600 Tel: +86 - 10 - 51265801

E-mail: international@sanew-cable.com

Fax: +86 - 10 - 51286576 Website: